



RH-10VSD

Fluxair Rotary Screw Compressor
Model: RH-10VSD (7.5kw 10hp)
Pressure: 7-10 Bar
Air Delivery: 0.90-1.2 m³/min (32-42 cfm)
Controller: MAM-6080M
Motor: Jiangtian IP55 Motor
Electricity: 380v 3phase 50Hz
Shipping: 900*625*860mm | 187kg

Cooling Method	Air Cooled
Discharge Pressure (Bar)	10 Bar
Drive Frequency	Variable Speed (VSD)
Discharge Temperature	Environment temp +15°C
Drive Type	Direct-Drive
Noise Level (dBa)	65~70±2 dB
Oil Contents in air (ppm)	≤3~5 ppm
Power (kW/hp)	7.5kW 10hp
Voltage/Frequency	380 V / 50 Hz / 3 Phase
Start-up Method	Variable Frequency Drive (VFD)
Motor Speed (rpm)	3000 rpm
Isolation Grade	Class F
Air Outlet Diameter (inches)	G3/4"
Air End	Baosi
Air Oil Separator	Fuhaihua
Intake/MPV	Nantong Redstar
Oil Filter	Airpull
AC Contactor	Schneider
Oil Separator	Airpull
Cooling Fan	Xingyi
Electric Motor	Jiangtian IP55 380V
Controller	MAM-6080M
Weight (kg)	187
Dimensions (mm)	900*625*860
Air Filter	201-TGA6054
Oil Filter	202-TGO506
Separator	115*90*135
Intake Valve	AIV-25YE
MPV	MPV-20JFM
Coupling	GR28 28*38
Main Shaft Seal	BST-55A-08