



RH-20FS

Fluxair Rotary Screw Compressor
Model: RH-20FS (15kw 20hp)
Pressure: 10 Bar
Air Delivery: 1.81 m³/min (64 cfm)
Controller: MAM-880
Motor: Jiangtian IP55 Motor
Electricity: 380v 3phase 50Hz
Shipping: 1050*700*1100mm | 285kg

Cooling Method	Air Cooled
Discharge Pressure (Bar)	10 Bar
Drive Frequency	Fixed Speed (FS)
Discharge Temperature	Environment temp +15°C
Drive Type	Direct-Drive
Noise Level (dBa)	65~70±2 dB
Oil Contents in air (ppm)	≤3~5 ppm
Power (kW/hp)	15kW 20hp
Voltage/Frequency	380 V / 50 Hz / 3 Phase
Start-up Method	Star Delta
Motor Speed (rpm)	2950 rpm
Isolation Grade	Class F
Air Outlet Diameter (inches)	G1"
Air End	Baosi
Air Oil Separator	Fuhaihua
Intake/MPV	Nantong Redstar
Oil Filter	Airpull
AC Contactor	Schneider
Oil Separator	Airpull
Cooling Fan	Xingyi
Electric Motor	Jiangtian IP55 380V
Controller	MAM-880
Weight (kg)	285
Dimensions (mm)	1050*700*1100
Air Filter	201-TGA6122
Oil Filter	202-TGO200
Separator	203-2140140ROT
Intake Valve	JIV-40BE
MPV	MPV-20JFM
Coupling	GR28 28*38
Main Shaft Seal	BST70A-07