



RH-30VSD

Fluxair Rotary Screw Compressor
Model: RH-30VSD (22kw 30hp)
Pressure: 7-10 Bar
Air Delivery: 3.11-3.6 m³/min (110-127 cfm)
Controller: MAM-6080m
Motor: Jiangtian IP55 Motor
Electricity: 380v 3phase 50Hz
Shipping: 1200*850*1145mm | 362kg

Cooling Method	Air Cooled
Discharge Pressure (Bar)	10 Bar
Drive Frequency	Variable Speed (VSD)
Discharge Temperature	Environment temp +15
Drive Type	Direct-Drive
Noise Level (dBa)	65~70±2 dB
Oil Contents in air (ppm)	≤3~5 ppm
Power (kW/hp)	22kW 30hp
Voltage/Frequency	380 V / 50 Hz / 3 Phase
Start-up Method	Variable Frequency Drive (VFD)
Motor Speed (rpm)	3000 rpm
Isolation Grade	Class F
Air Outlet Diameter (inches)	G1"
Air End	Baosi
Air Oil Separator	Fuhaihua
Intake/MPV	Nantong Redstar
Oil Filter	Airpull
AC Contactor	Schneider
Oil Separator	Airpull
Cooling Fan	Xingyi
Electric Motor	Jiangtian IP55 380V
Controller	MAM-6080M
Weight (kg)	362
Dimensions (mm)	1200*850*1145
Air Filter	201-TGA6122
Oil Filter	202-TGO200
Separator	203-2140202
Intake Valve	JIV-50B
MPV	MPV-25C-Y10
Coupling	L114 (G38) 40*42
Main Shaft Seal	BST-80A-08